



**HYDRAULIC COUPLINGS**  
HYDRAULIK KUPPLUNGEN

**SERIE 074F**

FLAT-FACE  
AGRICULTURAL COUPLER AGRAR-HYDRAULIK SERIE



**Couplers and Plugs**  
Kupplungen und Nippel

Connection  
Anschlüsse  
ØT


Order No  
Bestellnr.

L

LI


ØD

SW




Female Thread Coupler  
Kupplung mit Innengewinde

M 18x1.5	074F DGBM 18	56.5	47	27
M 20x1.5	074F DGBM 20	56.5	47	27
3/8"	074F DGB 17	56.5	47	27
1/2"	074F DGB 21	56.5	47	27



Male Thread Plugs  
Nippel mit Außengewinde

M 18x1.5	074F EUBM 18	51	23	220	32
M 20x1.5	074F EUBM 20	51	23	220	32
1/2"	074F EUB 21	43	15	220	32



Female Thread Plugs  
Nippel mit Innengewinde

1/2"	074F DUB 21	51		220	32
------	-------------	----	--	-----	----

**Interchangeability - Kompatibilität**

PARKER 5676 serie Hansen - Gromelle Serie 9000

**Temperature Range Temperaturbereich**

-20°C +100°C (-4°F +212°F)

**Working Pressure - Betriebsdruck**

Max. 220 bar - 3300 PSI (max.)

**Flow capacity - Nennweite**

NW Ø8 mm.

**Material - Material**

Main parts made of Steel  
Bichromated - Zing Plated  
All Highly Stressed component  
Are Hardened  
Seals - Nitrile (Ni) - NBR (Ni)  
Buck-Up Ring - PTFE

