


HYDRAULIC COUPLINGS
HYDRAULIK KUPPLUNGEN

SERIE 073

SUPER FLOW LINE **SUPERDURCHFLUSS**




Poppet valving serie - Tellerventil Serie




Couplers and Plugs Kupplungen und Nippel	Body Size Nennweite	Connection Anschlüsse (ØT)	Order No Bestellnr.	SW	Lenght - Lange		ØD
					L	Coupled Gekuppelt	
Coupler Body Kupplungs-Grundkörper	1/4"	NPT 1/4"	073 TGB 13	22	63.5	77	30
	3/8"	NPT 3/8"	073 TGB 17	25	72.5	87.5	35
	3/8"	BSP 3/8"	073 DGB 17	25	56.7		35
Plug Nippel	1/4"	NPT 1/4"	073 NUB 13	19	32.5	88	
	3/8"	NPT 3/8"	073 NUB 17	32	40	87.5	
	3/8"	BSP 3/8"	073 DUB 17	32	40		

Ball valving serie - Kugelventil Serie



Couplers and Plugs Kupplungen und Nippel	Body Size Baugröße	Connection Anschlüsse (ØT)	Order No Bestellnr.	SW	Lenght - Lange		ØD
					L	Coupled Gekuppelt	
Coupler Body Kupplungs-Grundkörper	1/4"	NPT 1/4"	073 TGB 13-1	22	58.8	73.3	30
	3/8"	NPT 3/8"	073 TGB 17-1	27	72	87.2	35
Plug Nippel	1/4"	NPT 1/4"	073 NUB 13-1	19	32.5	73.3	
	3/8"	NPT 3/8"	073 NUB 17-1	32	40	87.2	

Anti - Dust Cap / Staubdecke



For Couplers / Für Kupplungen

073 KG 13
073 KG 17



For Plugs / Für Nippel

073 KU 13
073 KU 17

Interchangeability - Kompatibilität
GROMELLE 56000, OTHER MANUFACTURER PRODUCTS

Temperature Range Temperaturbereich
-20 °C +100 °C (-4 °F +212 °F)
-20 °C +180 °C (-4 °F +370 °F)

Working Pressure - Betriebsdruck
0 - 700 bar (0 - 10000 PSI)

Flow capacity - Nennweite
NW - 1/4" - 3/8"

Standard version - Standardversion
Nitrile (Ni) - NBR (Ni)
Zinc plated - Verzinkt
Double shut off - Beideseitig absperierbar

Option - Optionen
F - Straight through flow - ungehinderter Durchfluss
S - Stainless Steel - Edelstahl
V - Viton Seal - Viton Dichtung

For optional orders please add the symbol of your option end of the order no.
Bei Optionsbestellungen Kennbuchstabe bitte hinzufügen (073 EG 13-1-K-V)

Material - Material

- Coupler Body-
Kupplungsgrundkörper : Steel Nickel Plated - Stahl vernickelt
- Sleeve - Hülse : Steel Nickel Plated - Stahl vernickelt
- Valve - Ventil : Brass - Messing
- Spring - Federn : Stainless Steel - Edelstahl
- Locking O-Ring-
Sprengring : Stainless Steel - Edelstahl
- Balls Kugeln : Stainless Steel - Edelstahl
Edelstah AISI 420l
- Seals - Dichtungen : Nitrile (Ni) - NBR (Ni)
- Plug - Nippel : Steel Nickel Plated - Stahl vernickelt